



2250 E. Tropicana Ave Phone: (866) 977-8833
 Suite 19-600 Fax: (800) 804-0182
 Las Vegas, NV 89119 Email: sales@polytuffus.com
 Web: www.polytuffus.com

E-TUFF® THIXO

Additive for E-Tuff® Membrane
 for Vertical Application

DESCRIPTION

E-Tuff® Thixo is an additive for E-Tuff® 100 base membranes for vertical applications. It provides vertical sag resistance of 100 mil.

FEATURES

- ❖ Non-Sag for Vertical Application
- ❖ Solvent Free
- ❖ TDI Free

TYPICAL USES

Vertical Application in Areas for:

- ❖ Water Damage
- ❖ Light Auto Traffic
- ❖ Pedestrian Traffic
- ❖ Ship Deck Overlays
- ❖ Concrete Bridges
- ❖ Concrete or Plywood Decks
- ❖ Most Metal, Rubber, Wood, or Masonry Surfaces

COLOR

Blue

PACKAGING

1 quart can for mixing with 1 gallon can of E-Tuff® 100.

1 gallon can for mixing with 5 gallon pail of E-Tuff® 100.

MIXING

E-Tuff® Thixo may NOT be diluted under any circumstances.

Using a mechanical mixer, first pre-mix separately E-Tuff® 100 and E-Tuff® Thixo thoroughly to obtain a uniform color, making sure to scrape the solids from the bottom and sides of the pail.

Pour E-Tuff® Thixo into E-Tuff® 100 slowly and while mixing, scrape the sides of the container. Mix for 1-2 minutes. Mix the combined E-Tuff® Thixo and E-Tuff® 100 mixture thoroughly until uniform color is obtained.

APPLICATION

Refer to E-Tuff® 100 Technical Bulletin.

TECHNICAL DATA

Parlance	Blue
Viscosity (@ 80°F)	28 ± 5
Specific Gravity	1.07 ± 0.1
Sag Resistance of Mixed Membrane	100 mils

STORAGE

E-Tuff® Thixo has a shelf life of six (6) months from date of manufacture in factory sealed containers.

Distributors and contractors, please rotate your stock.

LIMITATIONS

DO NOT allow E-Tuff® Thixo to freeze. Store between 40°F to 100°F.

E-Tuff® Thixo is not UV stable and is not designed to withstand direct wear/abrasion.

PSI does not recommend that E-Tuff® Thixo be diluted.

For complete information associated with the application of E-Tuff® Thixo, refer to System Specifications, Guidelines and Technical Bulletins.

Please read all information in the general guidelines, product data sheets, guide specifications and material safety data sheets (MSDS) before applying material. Published technical data and instructions are subject to change without notice. Contact your local PSI representative or visit our website for current technical data and instructions.

LIMITED WARRANTY

PSI warrants its products to be free of manufacturing defects and that they will meet PSI current published physical properties. PSI warrants that its products, when properly installed by a state licensed waterproofing contractor according to PSI guide specifications and product data sheets over a sound, properly prepared substrate, will not allow water migration for a period of 12 months. Seller's sole responsibility shall be to replace that portion of the product which proves to be defective. There are no other warranties by PSI of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. PSI shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. PSI shall not be responsible for use of this product in a manner to infringe on any patent held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and/or physical movement of the substrate or structural defects are also excluded from the limited warranty. PSI reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator.

DISCLAIMER

All guidelines, recommendations, statements, and technical data contained herein are based on information and tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. It is the users responsibility to satisfy himself, by his own information and test, to determine suitability of the product for his own intended use, application and job situation and user assumes all risk and liability resulting from his use of the product. We do not suggest or guarantee that any hazard listed herein are the only ones which may exist. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements, whether in writing or oral, other than those contained herein shall not be binding upon the manufacturer, unless in writing and signed by a corporate officer of the manufacturer. Technical and application information is provided for the purpose of establishing a general profile of the material and proper application procedures. Test performance results were obtained in a controlled environment and PSI makes no claim that these tests or any other tests, accurately represent all environments.